




## Transformer Connectors

# TC 2523 Si 20 - Conductor size 4 mm<sup>2</sup>, 1 pole fused connectors, (interlockable to any required length), for fuse links 5x20

<b>Approvals</b>			
<b>Nominal cross-section mm<sup>2</sup></b>		20-10 AWG 20 amp.	
<b>Voltage rating</b>	<b>V</b>	600	

## Technical data

<b>Connection</b>	screwless by spring cage terminal conductor size 0.5 - 4.0 mm <sup>2</sup> connection instructions as <a href="#">Internet-Download</a> and as package insert
<b>Fixing</b>	to snap-in devices of the winding frame
<b>Mouldings</b>	polyamide 6/6, orange or grey flammability rating to UL 94: V-2 continuous working temperature 100 °C short-time temperature 160 °C
<b>Contacts</b>	busbars: copper, tinned spring cage: stainless spring steel
<b>Current rating</b>	to EN 60127-6: up to 10 A at T 70 °C
<b>Stripping length</b>	9 - 10 mm
<b>Fuse size</b>	5 x 20 mm, power dissipation 2.5 W at T 23 °C
<b>Interlocking</b>	by lateral pins to any required length, to 1 and 3 pole connectors <a href="#">TC 2523</a> and <a href="#">2533</a>



## Order info

Description	Item	Order No.	PU
1 pole	TC 2523 Si-20 grey	258301	100
	TC 2523 Si-20 orange	258391	100

## Accessories

**TYP BZ 14, BZ 14 R and MT** Marking labels for all types, either label strips or breakable labels

## Upon request

1 pole fused connectors for fuse size 6.3 x 32 mm, without lateral pins, interlocking to any required lengths