



## AC 166® Classic 3 pole

# AC 166-1 BULH/3 Combinable Coding - 3 pole sockets with horizontal solder terminals

<b>Approvals</b>		
<b>Nominal cross-section mm<sup>2</sup></b>		2,5
<b>Voltage rating</b>	<b>V</b>	250

## Technical data

<b>Connection</b>	horizontal/rectangular connection to pc-board
<b>Mouldings</b>	polyamide 6/6, coral red (cover black) flammability rating to UL 94: V-2 continuous working temperature 100 °C short-time temperature 160 °C
<b>Contacts</b>	brass, plated
<b>Current rating</b>	to EN 61984: 16 A at T 70 °C
<b>Upper limit temperature</b>	to EN 61984: 110°C
<b>Length solder pin</b>	3.3 mm
<b>Eyelet/mounting hole</b>	Ø 1.4 mm



## Order info

Description	Item	Order No.	PU
<b>Sockets horizontal, without Latches</b>			
combinable coding (L1 PE N)	AC 166-1 BULH/ 3 coral red	1636X3	500
<b>Sockets horizontal, with Latches</b>			
combinable coding (L1 PE N)	AC 166-1 BULH/ 3 coral red with VSL	1636X3V	500

## Accessories

**AC 166 VSE, VSF, VSL** Latches

## Upon request

"180°"-version